

SMMS/SHRM: Corrosion Protection Model



SMMS/SHRM: Corrosion Protection Model

		Standard	Corrosion protection	
			(Light protection)	(Heavy protection)
Panel		Coated steel panel	Coated steel panel	Coated steel panel
Base Plate		Coated steel panel	Galvanized steel panel with acrylic resin paint (Inside/outside)	Galvanized steel panel with acrylic resin paint (Inside/outside)
Fan Guard		Polyethylene coating	Polyethylene coating	Polyethylene coating
Screw		Steel for screws + Chromate filming	SUS410, + Dacurionium filiming	SUS410, + Dacurionium filiming
Bolt		Steel for screws + Chromate filming	SUS410, + Dacurionium filiming	SUS410, + Dacurionium filiming
Heat Exchanger	Fin	Resin coating	Resin coating	Acrylic resin paint
	Copper Tube	Without treatment (Copper)	Without treatment (Copper)	Acrylic resin paint
	End Plate	Without treatment (Galvanised steel)	Epoxy coating paint	Acrylic resin paint
Fan		AS-G plastic	AS-G plastic	AS-G plastic
Fan motor		Polyester resin + Aluminium die cast	Polyester resin + Aluminium die cast	Polyester resin + Aluminium die cast
Electric Parts Box		Galvanized steel sheet	Galvanized steel sheet with additional acrylic resin paint	Galvanized steel sheet with additional acrylic resin paint
P.C.board		-	Insulation coating (solder side)	Insulation coating (solder side)
Piping		Copper	Copper (no modification)	Copper (no modification)

- 1) Corrosion protection model is assemble to order.
- 2) Consult our local dealer for model suitability or coastal environment.
- 3) Minimum quantity per model: 5 sets.
- 4) Standard Lead time: Order indication 4.5 months, Order confirmation 3 months before production / shipping months (to be confirmed per inquiry).